

# EVERBEING INT'L CORP.

Your Partner in Probing Solutions



## EB-6 Probe Station

State of the art probe station for all  
your DC and RF requirements

The EB series is our flagship probe station product line. It's features and foundation are solid for providing repeatable, accurate measurements in both DC and RF applications. :

### Features

- Low profile coaxial-driven style stage (optional large knob precision stage)
- Back-lash free movement
- Mounting for 12 micropositioners
- 4.5" Probe Card Holder compatible
- Micropositioner Standby Dock
- Microscope Tilting for E-Z lens switching

### Applications

- Basic IV/CV
- RF, Single Broadband Probing
- High Voltage, High Current

### Accessories

- Hot Chuck with Temperature Controller
- Vibration Free Table
- Shielding Box

 西華産業株式会社

東京都千代田区丸の内3-3-1新東京ビル3F  
西華産業株式会社 電子機器部  
当製品担当窓口/森本頼子(もりもとよりこ)  
TEL: +81-3-5221-7112  
morimotoy@jp.seika.com  
<https://www.seika.com/>

# EB-6 PROBE STATION

## Your Partner in Probing Solutions

### Station Specifications

Station Footprint	580 mm W x 460 mm D
Station Height	450 mm (to Platen)/700 mm (to Microscope)
Station Weight	60 kg
Platen Material	Hard Chrome Plated Steel
Platen Dimension	250 mm Inner, 450mm Outer
Platen Capacity	12 DC or 4 RF 4 DC
Positioner Mount	Magnetic ON/OFF Switch
No. of Vacuum Switches	4
Chuck Material	Stainless Steel
Chuck Stage Type	Coaxial (Large Knob Optional)
Chuck Travel Range	6" x 6"
Chuck Quick Resolution	25 mm/rev
Chuck Fine Resolution	1 $\mu$ m
Chuck Theta Coarse Travel	360°
Chuck Theta Fine Resolution	0.01°
Chuck Z-Motion	4 mm Range
Chuck Z Fine Resolution	1 $\mu$ m
Coaxial Chuck Movement	Bevelled Gear and Rack 0.8mm Pitch
Large Knob Chuck Movement	High Precision Linear Stage
Chuck Size	6" (150 mm)
Chuck Planarity	3 $\mu$ m
Chuck Rigidity	15 $\mu$ m / 10 N @ edge
Chuck Vacuum Grooves	Center, 1.5", 3", 5" (Individually Controlled)
Chuck Bias Capacity	Up to 2 kV
Chuck Isolation	5 G $\Omega$
DUT Size Range	2 mm - 150 mm
Microscope Stage Type	High Precision Linear Stage
Microscope Stage Resolution	1 $\mu$ m
Microscope Stage Travel Range	2" x 2"
Microscope Tilting (Optional)	35°
Microscope Zoom Range	1x - 5x
Microscope Eye Piece	20x
Microscope Magnification Range	20x-100x

# EB-6 PROBE STATION

## Micropositioner Options

All micropositioners offer X-Y-Z linear-motion travel with no backlash with mounting options including magnet, vacuum or magnet switch



### EB-050

**Resolution:** 0.8  $\mu\text{m}$

**Screw Resolution:** 212  $\mu\text{m}$

**Travel Range:** Linear 12 mm X-Y-Z

**Dimensions:** 52 mm W x 96 mm D x 76 mm H

**Weight:** 550 g

**Use For:** DC/RF Capable



### EB-700

**Resolution:** 2  $\mu\text{m}$


**Screw Resolution:** 630  $\mu\text{m}$

**Travel Range:** Linear 12 mm X-Y-Z

**Dimensions:** 38 mm W x 62 mm D x 45 mm H

**Weight:** 200 g

**Used For:** DC Only



### EB-005

**Resolution:** 0.3  $\mu\text{m}$

**Screw Resolution:** 125  $\mu\text{m}$

**Travel Range:** Linear 12 mm X-Y-Z

**Dimensions:** 90 mm W x 130 mm D x 90 mm H

**Weight:** 1000 g

**Used For:** DC/RF Capable

# EB-6 PROBE STATION

---


## Vibration Free Table Option

---



### VFT-3636

**Dimension:** 36" W x 36" D x 36" H  
**Vertical Natural Frequency:** 1.5 Hz  
**Isolation Efficiency:** @ 5 Hz 85%  
**Horizontal Natural Frequency:** 1.2 Hz  
**Isolation Efficiency:** @ 5 Hz 91%  
**Air Requirement:** 80 psi  
**Net Load:** 200 kg  
**Material:** Stainless Steel TableTop

 西華産業株式会社

東京都千代田区丸の内3-3-1新東京ビル3F  
西華産業株式会社 電子機器部  
当製品担当窓口/森本頼子(もりもとよりこ)  
TEL: +81-3-5221-7112  
morimotoy@jp.seika.com  
<https://www.seika.com/>

